



TASKI®

Tapi Defoam

Defoamer

Description

Defoamer recommended for use in spray extraction machines and wet vacuum cleaners. Prevents build up of foam in the pick up tank.

Key properties

- Fast defoaming action
- Suitable for all vacuum pick up tanks where foam control is required

Benefits

- Increases carpet cleaning efficiency
- Will not block machines due to foam development

Use instructions

Pour approximately 100ml directly into the pick-up/dirty water tank of the machine.

Dosage:

Ready to use, no dilution required.

Technical data

Appearance: Clear, colourless liquid

pH value (neat): N/A

pH value (in use): N/A

Relative density (20°C): 0.80 g/cm³

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diverseyl.com. Store in original closed containers away from extremes of temperature.

Only for professional users / specialists.

Product compatibility

Do not apply the product directly on the carpet (risks of staining from the solvents and fast re-soiling due to residues from the product).

Environmental information


Must not reach sewage water or drainage ditch undiluted or unneutralised.

Available pack sizes

TASKI Tapi Defoam is available in 6x1L.

www.diverseyl.com

© 2018 Diversey, Inc. All Rights Reserved. MASTER 41/18 P90782



© A.I.S.E.