



TASKI® Jontec Lenio

F5b

Water-based wax maintainer

Description

Water-based wax. Suitable for unprotected and protected floors wheather raw, oiled and varnished.

Key properties

- Cleans, maintains and protects
- Buffable, highly slip-resistant protective film
- Solvent-free
- Unique, patented Odour Neutralizing Technology (O.N.T.)

Benefits

- Protect floors against humidity in the grouts (especially raw and prevarnished parquets) and from premature wear
- Builds a safe to walk on and attractive silk-like protection
- Environmentally responsible and easy application (applicators/pads are easily rinsed with water)
- Leaves a pleasant, fresh fragrance
- Neutralises malodour molecules and therefore enhances the perfume effect

Use instructions

Shake well before use. Depending on floor traffic, the first use of the product may require several spray and buffing/densifying cycles in the beginning; cycle intervals can later be extended. Apply watery cleaning solutions very sparingly and always immediately pick up/wet vacuum.

Full surface cleaning/maintenance:



1. For sealed wood, add the product into the spray device of a single disc machine, equipped with red pad, and spray clean the floor. For unsealed wood apply one thin coat with a polish applicator.
2. Allow to dry, then immediately buff.
3. Unsealed wood floors may require a second coat (mat in between the 2 coats).
4. Allow to dry completely before applying additional coats.
5. After the floors has dried, buff the entire area with a white or red pad to densify the film.

Spray cleaning:

1. Add the product into the spray device of a single disc machine, equipped with an appropriate pad, and spray clean the floor.
2. After a short drying time, buff the whole surface for a more uniform appearance/gloss level.
3. Stripping: Spray clean the surface with TASKI Jontec Solve and a single disc machine, equipped with a blue pad.

Spot cleaning/maintenance:

1. Add the product into the spray device of a single disc machine, equipped with an appropriate pad, and spray clean the floor by spraying only on spots/soiled areas.
2. After a short drying time, buff the whole surface for a more uniform appearance/gloss level.



© A.I.S.E



TASKI® Jontec Lenio

F5b

Dosage*

Initial treatment, protection application:

Ready to use, no dilution required.

Single disc machine (spray method): 375 ml/750 ml (50%).

Maintaining application:

Single disc machine (spray method): 23 ml/750 ml (3%).

**This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.*

Technical data

Appearance: Milky, white liquid

Odour: Pine

pH value (neat): ≈ 4

Relative density (20°C): ≈ 1.00

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature. Only for professional users / specialists.

Do not store or use at temperatures below 5°C.

Approvals

Slip resistance 0.5 minimum (ASTMD D 2047).

Available pack sizes

TASKI Jontec Lenio is available in 2x5L.

www.diversey.com

© 2024 Diversey, Inc. All Rights Reserved. 03/07/2024 en (P90974)