

Suma Revoflow™ V3.0 System

Improved washing, outstanding results

The Revoflow MWW gives you:

- ▶ A Modular System
- ▶ Easy to Install
- ▶ Flexible
- ▶ Safe for User



Innovative

We know you want excellent results each and every time you wash. So we have used our in-depth knowledge to create Revoflow™ - a unique system that enhances the dishwashing experience, doing away with virtually all the hazards and inefficiencies of traditional dishwashing systems.

We understand your business and know just how important safety, cleanliness and cost efficiency are to you. With Revoflow™ you will find automated precision dosing, no chance of spillages, a compact off the floor design and less need for detailed staff training; this ultimately results in a more efficient workplace.

The real beauty of Revoflow™ is the innovative cap design. Colour coded to make sure the right chemical is consistently in the right place, it is designed for precision dosing and dispensing of liquids and powders, so there is no waste and no need to rewash. Every time a new container is fitted you also refresh the dosing accuracy, giving outstanding results each and every time. Combine Revoflow™ with Diversey's newly formulated Suma® detergents, customised to your specific needs, and you can be sure of perfect dishwashing... .. time after time.

Other Features:

- ▶ Ergonomic, modular and easy to install
- ▶ Closed system with low service requirements
- ▶ Safe, off the floor system for the user
- ▶ Easy to understand indicators
- ▶ Using ergonomics in chemical supply (4.5kg instead of heavy containers)
- ▶ Use of concentrate means less waste in packaging
- ▶ High performance as well as being economical

Suma Revoflow™ V3.0 Specifications

Technical Data

Specifications

Powder/Liquid Feeder

Height* x Width x Depth	440 x 142 x 230mm / 7 x 5.6 x 9.0in
*allow 160mm / 6in for removal of bottles	

Powder Feeder

Weight (Feeder only, no chemical)	2.1kg (4.6lbs)
Maximum Pressure	4.8 bar (70 psi)
Minimum Pressure	1.1 bar (15 psi)
Enclosure Material	PP, glass and talc fill
Delivery Tube (Powder Feeder)	16mm (5/8in) PU / Vinyl
Water Temperature Range (Powder)	6 - 65°C, 43 - 149°F

Liquid Feeder

Weight (Feeder only, no chemical)	1.4kg (3.0lbs)
Maximum Pressure	2.1 bar (30 psi)
Pump Tubing Material	3mm (1/8in) ID Flex
Delivery Tube Material	4mm / 1/8in PE

Controller Module

Height x Width x Depth	280 x 76 x 230mm / 11 x 3 x 9in
Weight	1.1 kg (2.43 lbs)
Power Ratings	65W, 100-240+/-10% 50-60Hz
Alarm Output	24V DC at 0.25A

Ordering Information

Description	Part Number
Global	
Controller	5520523
Powder Module	5520558
Liquid Module	5520566
1 Product Mounting kit	5548307
2 Product Mounting kit	5548315
3 Product Mounting kit	5548323
Electrical hook up kit	5548454
Detergent hook up kit	5548484
2 nd Powder module hook up kit	5548518
Liquid Low Flow (LF) kit	5548534
EMA Install	
EMA Water Hook Up kit	5548366
Valve non return NRV12 4mm (SAP)	65348
Valve non return NRV12 4mm (JDEd)	EQ0065348

Description	Part Number
NA Install	
NA Water Hook Up kit	5661342
NA Module Hook Up kit	5638118
Rinse hook up kit	5548526
Additional Optional Installation items	
Conductivity Probe - NA & APAC (SAP)	18079
Conductivity Probe - NA & APAC (JDEd)	E454020
Conductivity Probe D42 (SAP)	35395
Conductivity Probe D42 (JDEd)	E454036
System Spares	
Univew (SAP)	58017
Uniview (JDEd)	E070027
For Regional Specific Spares:	
Please see TCS Documentation	

Engineering Services
Dosing, Dilution & Dispensing, Engineering
Diversey Global RD&E

Americas Tel+1-262-631-4660
EMA Tel+44-(0)1623-728010
APAT & Japan Tel+44-(0)1623-728064

Americas & GAPAC
Diversey Equipment
370 Encinal Street
Santa Cruz, CA 95060
U.S.A.
Tel +1-831-457-5790
Fax +1-831-471-3587

Diversey Equipment is ISO 9001 Certified
<http://www.diversey.com>

EMA
Diversey Equipment
4 Finway Dallow Road
Luton LU1 1TR
United Kingdom
Tel +44 -(0)1582-702191
Fax +44 -(0)1582-702104

